

Thyborønvej 78 DK-7673 Harboøre

Denmark +45 9690 9690 www.fmc.com

CVR No. DK 12 76 00 43

Material group		Page 1 of 14
Product name	BIPLAY SX	
		November 2017
Safety data sheet according to EU Reg. 1907/2006 as amended		Supersedes 03.11.2017

SAFETY DATA SHEET **BIPLAY SX**

Revision: Sections containing a revision or new information are marked with a .

▲ SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier **BIPLAY SX**

1.2. Relevant identified uses of the substance or mixture and uses

advised against Can be used as herbicide only.

1.3. Details of the supplier of the safety

data sheet

CHEMINOVA A/S, a subsidiary of FMC Corporation

Thyborønvej 78 DK-7673 Harboøre

Denmark

SDS.Ronland@fmc.com

1.4. Emergency telephone number

Medical emergencies:

Austria: +43 1 406 43 43 Norway: +47 22 591300 Poland: +48 22 619 66 54 Belgium: +32 70 245 245 Bulgaria: +359 2 9154 409 +48 22 619 08 97

Cyprus: 1401

Czech Republic: +420 224 919 293

+420 224 915 402

Romania: +40 21318 3606 Denmark: +45 82 12 12 12 Slovakia: +421 2 54 77 4 166 Slovenia: +386 41 650 500 France: +33 (0) 1 45 42 59 59

Finland: +358 9 471 977 Spain: +34 91 562 04 20 Greece: 30 210 77 93 777 Hungary: +36 80 20 11 99 112

Ireland (Republic): +352 1 809 2166 Italy: +39 02 6610 1029

Lithuania: +370 523 62052 +370 687 53378

Luxembourg: +352 8002 5500 Netherlands: +31 30 274 88 88 South Africa: +27 83 123 3911 (Bateleur Emergency Response Co.)

Sweden: +46 08-331231

Switzerland: 145

United Kingdom: 0870 600 6266 (in the UK only) U.S.A. & Canada: +1 800 / 331-3148 (ProPharma)

All other countries: +1 651 / 632-6793 (ProPharma - Collect)

For fire, leak, spill or other accident emergencies:

U.S.A.: +1 800 / 424 9300 (CHEMTREC)

Portugal: 808 250 143 (in Portugal only) +351 21 330 3284

All other countries: +1 703 / 527 3887 (CHEMTREC - Collect)



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	-	Page 2 of 14
Product name	BIPLAY SX	November 2017

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Health hazards

Hazards to the aquatic environment, acute: Category 1 (H400) chronic Category 1 (H410)

WHO classification Class U (unlikely to present acute hazard in normal use).

The product is not expected to cause severe adverse effects to health, but adverse health effects cannot be excluded in case of massive

exposure.

2.2. Label elements

According to EU Reg. 1272/2008 as amended

Product identifier Biplay SX

Hazard pictogram (GHS09)



Signal word Warning

Hazard statement

H410 Very toxic to aquatic life with long lasting effects.

Supplementary hazard statements

EUH208 Contains tribenuron-methyl. May produce an allergic reaction.

instructions of use.

Precautionary statements

P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/container as hazardous waste.

or vPvB.

♣ SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. **Substances** The product is a mixture, not a substance.

3.2. **Mixtures** See section 16 for full text of hazard statements.

Active ingredients

Tribenuron-methyl Content: 22% by weight



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	-	Page 3 of 14
Product name	BIPLAY SX	
		November 2017

CAS name	Benzoic acid, 2-[[[[(4-methoxy-6-methyl-1,3,5-triazin-2-yl)methyl-			
CAS no.	amino]carbonyl]amino]sulfonyl]-, methyl ester 101200-48-0			
IUPAC name	Methyl 2-[4-methoxy-6-methyl-1,3,5-triazin-2-yl(methyl)carbamoyl-			
TOT AC hame	sulfamoyl]		ictify1-1,5,5-tf1a2i	m-2-yi(metriyi)carbamoyi-
ISO name/EU name	Tribenuror			
EC no.		o: 401-190-1		
EU index no.			67/548/EEC: 613	3-265-00-3
Le mack no			1272/2008: 607-1	
Molecular weight	395.4	different to Iteg.	1272/2000:007	.,, 00)
Classification of the ingredient		isation: Catego	rv 1B (H317)	
companion of the ingression ini				Category 1 (H400)
				c: Category 1 (H410)
			*	
Metsulfuron-methyl	Content: 1	1% by weight		
CAS name			thoxy-6-methyl-1	,3,5-triazin-2-yl)amino]-
		mino]sulfonyl]		• • • • • • • • • • • • • • • • • • • •
CAS no	74223-64-6		•	
IUPAC name(s)	Methyl 2-(4-methoxy-6-m	nethyl-1,3,5-triazi	n-2-ylcarbamoyl-
	sulfamoyl)	benzoate	•	
ISO name/EU name	Metsulfuro	n-methyl		
EC no. (EINECS no.)	None	-		
EU index no	613-139-0	0-2		
Molecular weight	381.4			
Classification of the ingredient	Hazards to	the aquatic env	rironment, acute:	Category 1 (H400)
			chroni	c: Category 1 (H410)
Reportable ingredients	Content	CAS no.	EC no.	Classification
	(% w/w)		(EINECS no.)	
Sodium carbonate	5 - 10	497-19-8	207-838-8	Eye Irrit. 2 (H319)
Reg. no. 01-2119485498-19	5 10	177 17 0	207 030 0	Eye IIII. 2 (11315)
Reg. no. 01 2113 103 130 13				
Phosphoric acid, trisodium salt,	1 - 5	10101-89-0	231-509-8	Skin Irrit. 2 (H315)
dodecahydrate	1 0	10101 05 0	201 000 0	Eye Irrit. 2 (H319)
Reg. no. 01-2119489800-32				STOT SE 3 (H335)
.6				
Lignosulfonic acid, sodium salt,	1 - 5	68512-34-5	None	Eye Irrit. 2 (H319)
sulfomethylated				÷ , , , ,
-				
CTION A. FIRST AID MEASURES				

* SECTION 4: FIRST AID MEASURES

4.1.	Description of first aid measures Inhalation	If experiencing any discomfort, immediately remove from exposure. Light cases: Keep person under surveillance. Get medical attention immediately if symptoms develop. Serious cases: Get medical attention immediately or call for an ambulance.
	Skin contact	Immediately remove contaminated clothing and footwear. Flush skin with water. Wash with water and soap. See physician if any symptom develops.



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	-	Page 4 of 14
Product name	BIPLAY SX	
		November 2017

	Eye contact	Immediately rinse eyes with much water or eyewash solution, occasionally opening eyelids, until no evidence of chemical remains. Remove contact lenses after a few minutes and rinse again. See physician if irritation persists.
	Ingestion	Inducing vomiting is not recommended. Rinse mouth and drink water or milk. If vomiting does occur, rinse mouth and drink fluids again. Call a doctor or get medical attention immediately.
4.2.	Most important symptoms and effects, both acute and delayed	None known. Generally, sulphonylurea herbicides cause lethargy, confusion, dizziness, seizures and coma on ingestion of large quantities.
4.3.	Indication of any immediate medical attention and special	Immediate medical attention is required in case of ingestion
	treatment needed	It may be helpful to show this safety data sheet to physician.
	Note to physician	A specific antidote against this substance is not known. Gastric lavage and/or administration of activated charcoal can be considered. After decontamination, treatment is supportive and symptomatic.

♣ SECTION 5: FIRE-FIGHTING MEASURES

5.1.	Extinguishing media	Dry chemical or carbon dioxide for small fires, water spray or foam for large fires. Avoid heavy hose streams.
5.2.	Special hazards arising from the substance or mixture	The essential breakdown products are volatile, toxic, irritant and inflammable compounds such as nitrogen oxides, sulphur dioxide, carbon monoxide, carbon dioxide and phosphorous pentoxide.
5.3.	Advice for firefighters	Use water spray to keep fire-exposed containers cool. Approach fire from upwind to avoid hazardous vapours and toxic decomposition products. Fight fire from protected location or maximum possible distance. Dike area to prevent water runoff. Firemen should wear self-contained breathing apparatus and protective clothing.

♣ SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

It is recommended to have a predetermined plan for the handling of spills. Empty, closable vessels for the collection of spills should be available.

In case of large spill (involving 10 tonnes of the product or more):

- 1. use personal protection equipment; see section 8
- 2. call emergency telephone no.; see section 1
- 3. alert authorities.

Observe all safety precautions when cleaning up spills. Use personal protection equipment. Depending on the magnitude of the spill this



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	-	Page 5 of 14
Product name	BIPLAY SX	
		November 2017

may mean wearing respirator, face mask or eye protection, chemical resistant clothing, gloves and rubber boots.

Stop the source of the spill immediately if safe to do so. Reduce and avoid formation of airborne dust as much as possible, if appropriate by moistening.

6.2. Environmental precautions

Contain the spill to prevent any further contamination of surface, soil or water. Wash waters must be prevented from entering surface water drains. Uncontrolled discharge into water courses must be alerted to the appropriate regulatory body.

6.3. Methods and materials for containment and cleaning up

It is recommended to consider possibilities to prevent damaging effects of spills, such as bunding or capping. See GHS (Annex 4, Section 6).

Surface water drains should be covered if appropriate. Minor spills on the floor or other impervious surface should immediately be swept up or preferably vacuumed up using equipment with high efficiency final filter. Transfer to suitable containers. Clean area with strong industrial detergent and much water. Absorb wash liquid onto inert absorbent such as universal binder, Fuller's earth, bentonite or other absorbent clay and collect in suitable containers. The used containers should be properly closed and labelled.

Large spills which soak into the ground should be dug up and transferred to suitable containers.

Spills in water should be contained as much as possible by isolation of the contaminated water. The contaminated water must be collected and removed for treatment or disposal.

6.4. Reference to other sections

See subsection 8.2. for personal protection. See section 13 for disposal.

***** SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

In an industrial environment, it is recommended to avoid all personal contact with the product, if possible by using closed systems with remote system control. The material should be handled by mechanical means as much as possible. Adequate ventilation or local exhaust ventilation is required. The exhaust gases should be filtered or treated otherwise. For personal protection in this situation, see section 8.

For its use as a pesticide, first look for precautions and personal protection measures on the officially approved label on the packaging or for other official guidance or policy in force. If these are lacking, see section 8.



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	-	Page 6 of 14
Product name	BIPLAY SX	
		November 2017

Avoid contact with eyes, skin or clothing. Avoid breathing dust or spray mist.

Remove contaminated clothing immediately. Wash thoroughly after handling. Before removing gloves, wash them with water and soap. After work, take off all work clothes and footwear. Take a shower, using water and soap. Wear only clean clothes when leaving job. Wash protective clothing and protective equipment with water and soap after each use.

Do not discharge to the environment. Do not contaminate water when disposing of equipment wash waters. Collect all waste material and remains from cleaning equipment, etc., and dispose of as hazardous waste. See section 13 for disposal.

7.2. Conditions for safe storage, including any incompatibilities

The product is stable under normal conditions of warehouse storage.

Keep in closed, labelled containers. The storage room should be constructed of incombustible material, closed, dry, ventilated and with impermeable floor, without access of unauthorised persons or children. The room should only be used for storage of chemicals. Food, drink, feed and seed should not be present. A hand wash station should be available.

7.3. **Specific end use(s)**

The product is a registered pesticide which may only be used for the applications it is registered for, in accordance with a label approved by the regulatory authorities.

♣ SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

other component in this product. An exposure limit of 10 mg/m³ (8-hr TWA) is recommended for other sulphonylureas. However, personal exposure limits defined by local regulations may exist and must be

observed.

Tribenuron-methyl

DNEL, systemic 0.07 mg/kg bw/day

PNEC, aquatic environment 0.1 µg/l

Metsulfuron-methyl

DNEL, dermal 0.7 mg/kg bw/day

PNEC, aquatic environment 16 ng/l

Sodium carbonate



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

N	laterial group	-	Page 7 of 14
P	roduct name	BIPLAY SX	
			November 2017

be required. The following is meant for other situations, when the use of a closed system is not possible, or when it is necessary to open the system. Consider the need to render equipment or piping systems non-hazardous before opening.

The precautions mentioned below are primarily meant for handling of the undiluted product and for preparing the spray solution, but can be recommended for spraying as well.

In cases of incidental high exposure, maximal personal protection equipment may be necessary, such as respirator, face mask, chemical resistant coveralls.



Respiratory protection

The product does not automatically present an airborne exposure concern during normal handling, but in the event of an accidental discharge of the material which produces a heavy vapour or dust, workers must put on officially approved respiratory protection equipment with a universal filter type including particle filter.



Protective gloves

Wear chemical resistant gloves, such as barrier laminate, butyl rubber, nitrile rubber or viton. The breakthrough times of these materials for the product are unknown, but it is expected that they will give adequate protection.



Eye protection

Wear safety glasses. It is recommended to have an eye wash fountain immediately available in the workplace when there is a potential for eye contact.



Other skin protection

Wear appropriate chemical resistant clothing to prevent skin contact depending on the extent of exposure. During most normal work situations where exposure to the material cannot be avoided for a limited time span, waterproof pants and apron of chemical resistant material or coveralls of polyethylene (PE) will be sufficient. Coveralls of PE must be discarded after use if contaminated. In cases of excessive or prolonged exposure, coveralls of barrier laminate may be required.

♣ SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. **Information on physical and chemical properties**

Appearance Light brown to brown solid (granules)

pH 10 g/l dispersion in water: 9.7

Flammability (solid/gas) Not highly flammable (does not sustain combustion)



Thyborønvej 78 DK-7673 Harboøre

Denmark +45 9690 9690 www.fmc.com

CVR No. DK 12 76 00 43

Material group	-	Page 8 of 14
Product name	BIPLAY SX	
		November 2017

Upper/lower flammability or

explosive limits Not determined

Metsulfuron-methyl : $1.1 \times 10^{-10} \text{ Pa at } 20^{\circ}\text{C}$ 3.3 x $10^{-10} \text{ Pa at } 25^{\circ}\text{C}$

Bulk density, packed: 0.690 g/cm³

Solubility(ies) Solubility of **tribenuron-methyl** in:

acetone 43.8 g/l hexane 0.028 g/l

water 0.028 g/l at pH 4 and 25°C

0.050 g/l at pH 5 and 25°C 0.280 g/l at pH 6 and 25°C 2.040 g/l at pH 7 and 20°C

Solubility of **metsulfuron-methyl** at 25°C in:

 $\begin{array}{ccc} \text{n-hexane} & 0.584 \text{ mg/l} \\ \text{ethyl acetate} & 11.1 \text{ g/l} \end{array}$

water 0.55 g/l at pH 5 2.79 g/l at pH 7

213 g/l at pH 9

Partition coefficient n-octanol/water **Tribenuron-methyl** : $\log K_{ow} = 2.3$ at pH 1.5

 $\begin{array}{l} log~K_{ow} = 2.25~at~pH~4.0 \\ log~K_{ow} = 2.0~at~pH~5.0 \\ log~K_{ow} = 1.25~at~pH~6.0 \\ log~K_{ow} = -0.44~at~pH~7.0 \end{array}$

Metsulfuron-methyl : $\log K_{ow} = -1.7$ at pH 7 and 25°C

Decomposition temperature **Tribenuron-methyl** : 137.5 ± 0.5 °C

9.2. Other information

Miscibility The product can be dispersed in water.

♣ SECTION 10: STABILITY AND REACTIVITY

temperatures.

10.3. **Possibility of hazardous reactions** None known.

10.4. **Conditions to avoid** Heating of the product may evolve harmful and irritant vapours.

10.5. **Incompatible materials** None known.

10.6. **Hazardous decomposition products** See subsection 5.2.



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	-	Page 9 of 14
Product name	BIPLAY SX	
		November 2017

♣ SECTION 11: TOXICOLOGICAL INFORMATION

distribution

1. Information on toxicological effec	* = Based on available data, the classification criteria are not met.
Product Acute toxicity	The product is not harmful by inhalation, in contact with skin or if swallowed. * However, it should always be treated with the usual care of handling chemicals. The acute toxicity is measured as:
Route(s) of entry - ingestion	LD ₅₀ , oral, rat: > 5000 mg/kg (fixed dose method)
- skin	LD_{50} , dermal, rabbit: > 5000 mg/kg (method OECD 402)
- inhalation	LC ₅₀ , inhalation, rat: not available
Skin corrosion/irritation	Not irritating to skin (method OECD 404). *
Serious eye damage/irritation	Not irritating to eyes (method OECD 405). *
Respiratory or skin sensitisation	Not a skin sensitizer (method OECD 406). *
Germ cell mutagenicity	The product contains no ingredients known to be mutagenic. *
Carcinogenicity	The product contains no ingredients known to be carcinogenic. *
Reproductive toxicity	The product contains no ingredients found to have adverse effects on reproduction. *
STOT – single exposure	To our knowledge, no specific effects have been observed after single exposure. *
STOT – repeated exposure	The following has been measured on the active ingredient tribenuron-methyl: Target organ: liver LOEL: 300 mg/kg bw/day in a 90-day rat study (method OECD 407). At this exposure, increased liver weight and serum ALT levels were found. *
Aspiration hazard	The product contains no ingredients known to present an aspiration pneumonia hazard. *
Symptoms and effects, acute and delayed	To our knowledge, adverse effects in humans have not been reported. The product is not expected to cause severe adverse effects to health, but adverse health effects cannot be excluded in case of massive exposure. Generally, sulphonylurea herbicides cause lethargy, confusion, dizziness, seizures and coma on ingestion.
<u>Tribenuron-methyl</u>	
Toxicokinetics, metabolism and	Tribenuron-methyl is rapidly absorbed after oral intake, widely

distributed in the body and extensively metabolised. Excretion is



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Mat	erial group	-	Page 10 of 14
Proc	duct name	BIPLAY SX	
			November 2017

			rapid, within a few days. No indication of bioaccumulation is found.
	Acute toxicity		The substance is not harmful by inhalation, in contact with skin or if swallowed. * However, it should always be treated with the usual care of handling chemicals. The acute toxicity is measured as:
	Route(s) of entry	- ingestion	LD_{50} , oral, rat: > 5000 mg/kg (method OECD 425)
		- skin	LD_{50} , dermal, rat: > 5000 mg/kg (method OECD 402)
		- inhalation	LC_{50} , inhalation, rat: > 5.14 mg/l/4 h (method OECD 403)
	Skin corrosion/irritati	on	The substance may be slightly irritating to skin (method OECD 404). *
	Serious eye damage/in	rritation	The substance may be mildly irritating to eyes (method OECD 405). *
	Respiratory or skin se	ensitisation	The substance was found to be a weak sensitiser in guinea pigs (method OECD 406). It was not sensitizing in the Local Lymph Node Assay (method OECD 429).
Metsulfuron-methyl Toxicokinetics, metabolism and distribution			Metsulfuron-methyl is rapidly absorbed after oral intake. It is widely distributed in the body. It is partially metabolised. Excretion is rapid, within a few days. No indication of bioaccumulation is found.
	Acute toxicity		The substance is not harmful by inhalation, in contact with skin or if swallowed. * However, it should always be treated with the usual care of handling chemicals. The acute toxicity is measured as:
	Route(s) of entry	- ingestion	LD ₅₀ , oral, rat: > 5000 mg/kg (method 40 CFR 163-81-1)
		- skin	LD_{50} , dermal, rabbit: > 2000 mg/kg (method 40 CFR 163-81-2)
		- inhalation	LC_{50} , inhalation, rat: $> 5.0 \text{ mg/l/4 h}$ (method EEC B2)
	Skin corrosion/irritati	on	Not irritating to skin (method FIFRA 81.5). *
	Serious eye damage/in	rritation	The substance may be mildly irritating to eyes (method FIFRA 81.4).
Respiratory or skin sensitisation		ensitisation	The substance was not a sensitizer to guinea pigs (method OECD 406). *
Sodium carbonate Toxicokinetics, metabolism and distribution		polism and	Both sodium and carbonate ions are normal constituents in the body and regulated between narrow ranges. These ranges will not be exceeded, except locally in unusual situations such as accidents.
	Acute toxicity		The substance is not considered to be harmful by ingestion, inhalation or in contact with skin. *
	Route(s) of entry	- ingestion	LD ₅₀ , oral, rat: 2800 mg/kg
		- skin	LD ₅₀ , dermal, rabbit: > 2000 mg/kg



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com

CVR No. DK 12 76 00 43

Material group	-	Page 11 of 14
Product name	BIPLAY SX	
		November 2017

- inhalation LC₅₀, inhalation, rat: not available

Skin corrosion/irritation Not irritating to skin (method OECD 404). *

Serious eye damage/irritation Several tests have been performed with varying results. The weight of

evidence is that the substance is irritating to eyes.

Respiratory or skin sensitisation ... To our knowledge, no indications of allergenic effects have been

reported. *

Lignosulfonic acid, sodium salt, sulfomethylated

Route(s) of entry - ingestion LD_{50} , oral, rat: not available

- skin LD_{50} , dermal, rat: not available - inhalation LC_{50} , inhalation, rat: not available

Serious eye damage/irritation Causes serious eye irritation.

SECTION 12: ECOLOGICAL INFORMATION

as non-toxic to fish, aquatic invertebrates, soil micro- and

macroorganisms, birds, mammals and insects.

The ecotoxicity of the product is measured as:

Bees (Apis mellifera)

 $48-h LD_{50}$, oral: > 0.1 mg/kg

46-11 LD₅₀, 01a1. > 0.1 mg/kg

48-h LD₅₀, contact: > 0.11 mg/kg

12.2. Persistence and degradability

- Insects

Tribenuron-methyl is not persistent in the environment. Primary degradation half-lives vary with circumstances, from a few days to a few weeks in aerobic water and soil. Its metabolites are considered as persistent.

Metsulfuron-methyl does not meet the criteria for being readily biodegradable. It is moderately persistent in the environment. Primary degradation half-lives vary with circumstances, from a few weeks to a few months in aerobic soil and water. Degradation occurs both by chemical hydrolysis and by microbiological degradation.

The product contains minor amounts of not readily biodegradable



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	-	Page 12 of 14
Product name	BIPLAY SX	
		November 2017

		components, which may not be degradable in waste water treatment plants.
12.3.	Bioaccumulative potential	See section 9 for n-octanol/water partition coefficients.
		Due to high solubility in water, none of the active ingredients bioaccumulate.
12.4.	Mobility in soil	Under normal conditions tribenuron-methyl is of high to intermediate mobility in soil.
		Under normal conditions metsulfuron-methyl is mobile in soil. It has a potential for leaching to groundwater.
12.5.	Results of PBT and vPvB assessment	None of the ingredients meets the criteria for being PBT or vPvB.
12.6.	Other adverse effects	Other relevant hazardous effects in the environment are not known.
• OF	CTION 12 DISDOCAL CONSIDED	FIONG

♣ SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods		Remaining quantities of the material and empty but unclean packaging
		should be regarded as hazardous waste.

Disposal of waste and packagings must always be in accordance with all applicable local regulations.

Disposal of product

According to the Waste Framework Directive (2008/98/EC), possibilities for reuse or reprocessing should first be considered. If this is not feasible, the material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing.

Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Disposal of packaging

It is recommended to consider possible ways of disposal in the following order:

- 1. Reuse or recycling should first be considered. Reuse is prohibited except by the authorisation holder. If offered for recycling, containers must be emptied and triply rinsed (or equivalent). Do not discharge rinsing water to sewer systems.
- 2. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.
- 3. Delivery of the packaging to a licensed service for disposal of hazardous waste.
- 4. Disposal in a landfill or burning in open air should only occur as a last resort. For disposal in a landfill, containers should be emptied completely, rinsed and punctured to make them unusable for other purposes. If burned, stay out of smoke.



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	-	Page 13 of 14
Product name	BIPLAY SX	
		November 2017

SECTION 14: TRANSPORT INFORMATION

ADR/RID/IMDG/IATA/ICAO classification

14.2. **UN proper shipping name** Environmentally hazardous substance, solid, n.o.s. (tribenuron-methyl,

metsulfuron-methyl)

14.3. Transport hazard class(es) 9

14.4. Packing group III

14.5. Environmental hazards Marine pollutant

14.6. **Special precautions for user** Avoid any unnecessary contact with the product. Misuse can result in

damage to health. Do not discharge to the environment.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the

IBC code The product is not transported in bulk by ship.

♣ SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category (Dir. 2012/18/EU): dangerous for the environment.

All ingredients are covered by EU chemical legislation.

15.2. Chemical safety assessment

A chemical safety assessment is not required to be included for this

product.

SECTION 16: OTHER INFORMATION

Relevant changes in the safety data sheet

Minor corrections only.

List of abbreviations ALT Alanine transaminase

CAS Chemical Abstracts Service CFR Code of Federal Regulations

Dir. Directive

DNEL Derived No Effect Level EC European Community EC₅₀ 50% Effect Concentration

E_rC₅₀ 50% Effect Concentration based on growth

EINECS European INventory of Existing Commercial Chemical

Substances

ELINCS European LIst of Notified Chemical Substances FIFRA Federal Insecticide, Fungicide and Rodenticide Act

GHS Globally Harmonized classification and labelling System of



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	_	Page 14 of 14
Product name	BIPLAY SX	
		November 2017

	IBC ISO IUPAC LC ₅₀ LD ₅₀ LOEL MARPOL n.o.s. OECD PBT PNEC Reg. STOT TWA vPvB WHO	chemicals, Fifth revised edition 2013 International Bulk Chemical code International Organisation for Standardization International Union of Pure and Applied Chemistry 50% Lethal Concentration 50% Lethal Dose Lowest Observed Effect Level Set of rules from the International Maritime Organisation (IMO) for prevention of sea pollution Not otherwise specified Organisation for Economic Cooperation and Development Persistent, Bioaccumulative, Toxic Predicted No Effect Concentration Registration, or Regulation Specific Target Organ Toxicity Time Weighed Average very Persistent, very Bioaccumulative World Health Organisation
References		sured on the product are unpublished company data. Data on as are available from published literature and can be found aces.
Method for classification	Test data	
Used hazard statements	H315 H317 H319 H335 H400 H410 EUH208	Cause skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Contains tribenuron-methyl. May produce an allergic reaction. To avoid risks to human health and the environment, comply with the instructions of use.
Advice on training		rial should only be used by persons who are made aware of ous properties and have been instructed in the required cautions.

The information provided in this safety data sheet is believed to be accurate and reliable, but uses of the product vary and situations unforeseen by FMC Corporation may exist. The user has to check the validity of the information under local circumstances.

Prepared by: FMC Corporation / Cheminova A/S / GHB